



“Compounding for the Best”

CPE-01-266LT

Application: 90°C, oil resistant CPE based, FT4, 210,000 BTU wire and cable jacketing material with enhanced low temperature properties.

PRODUCT SPECIFICATIONS

Property	Units	Value	Test Method
Specific Gravity	g/cm ³	1.34 (±0.03)	ASTM D792
Durometer	Shore A	95/90 (±3)	ASTM D2240
Tensile Strength	PSI	1800	ASTM D412
Elongation	%	300	ASTM D412
Oxygen Index	%	39 min	ASTM D2863
Brittle Point	°C	-36 max	ASTM D746

Our Staff is available to answer questions and provide technical assistance at (978) 537-8261

140 Leominster-Shirley Road | Lunenburg, MA 01462 | 978.537.8261
Sales Fax: 978.534.8362 | General Fax: 978.537.5310 | www.sespoly.com

9/4/09

The information presented here is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise. All risks of such use are assumed by the user. Furthermore, nothing contained herein shall be construed as an inducement or recommendation to use any process or to manufacture or use any product in conflict with existing or future patents.