

“Compounding for the Best”

G-04-036ESD

Application: High Performance, PVC based compound with antistatic properties. G-04-036ESD is suitable for Gamma radiation sterilization.

PRODUCT SPECIFICATIONS

| Property | Units | Value | Test Method |
|---------------------|-------------------|--------------------|-------------|
| Durometer | Shore A | 76/70 (±3) | ASTM D2240 |
| Specific Gravity | g/cm ³ | 1.30 (±0.03) | ASTM D792 |
| Tensile Strength | psi | 1500 min | ASTM D412 |
| Elongation | % | 300 min | ASTM D412 |
| Surface Resistivity | ohm-cm | 1x10 ¹⁰ | ASTM D257 |
| Taber Abrasion | mg/1000 cycles | 180 | ASTM D1044 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

**Our Staff is available to answer questions and provide technical assistance at
(978) 537-8261**

140 Leominster-Shirley Road | Lunenburg, MA 01462 | 978.537.8261
Sales Fax 978.534.8362 | General Fax 978.537.5310 | www.sespoly.com

08/25/2009

The information presented here is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise. All risks of such use are assumed by the user. Furthermore, nothing contained herein shall be construed as an inducement or recommendation to use any process or to manufacture or use any product in conflict with existing or future patents.