

“Compounding for the Best”

GPP6025

Application: Specially engineered, low bloom, low specific gravity, flame retardant polypropylene compound designed with halogen based technology. Exhibits a unique balance of high flexural modulus and high impact. It is designed for use in injection molded industrial power supply systems and to meet their stringent criterion. The superior balance of flow, allows the material to maintain excellent aesthetics over long flow lengths. Available in a wide spectrum of colors.

PRODUCT SPECIFICATIONS

Property	Units	Value	Test Method
Specific Gravity	g/cm ³	1.27 – 1.31	ASTM D792
Melt Flow Rate	g/10 min	16 - 20	ASTM D1238
Tensile Strength @ Yield	PSI	2,500 min.	ASTM D638
Ultimate Elongation	%	50 min.	ASTM D638
Flexural Modulus	PSI	240,000 min.	ASTM D790
Flammability	1/16"	V-0	UL 94
Impact, Dart	ft-lb/in	6.0 min	ASTM D5420

Our Staff is available to answer questions and provide technical assistance at (978) 537-8261

140 Leominster-Shirley Road | Lunenburg, MA 01462 | 978.537.8261
 Sales Fax 978.534.8362 | General Fax 978.537.5310 | www.sespoly.com

6/19/2009

The information presented here is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise. All risks of such use are assumed by the user. Furthermore, nothing contained herein shall be construed as an inducement or recommendation to use any process or to manufacture or use any product in conflict with existing or future patents.