



“Compounding for the Best”

GTPR-1358A

Application: Thermoplastic Rubber material designed for winter boot applications requiring excellent abrasion and stitch tear. Available in a wide range of colors.

PRODUCT SPECIFICATIONS

Property	Units	Value	Test Method
Durometer, 15 sec	Shore A	54 (±3)	ASTM D2240
Specific Gravity	g/cm ³	1.05 (±0.03)	ASTM D792
Tensile Strength	PSI	650	ASTM D412
Elongation	%	550	ASTM D412
Rosflex, Cut Growth @ 10,000 flexes	%	0	ASTM D1052
Melt Flow Index, 2.16kg @ 190°C	g/10 min	10	ASTM D1238

Our Staff is available to answer questions and provide technical assistance at (978) 537-8261

140 Leominster-Shirley Road | Lunenburg, MA 01462 | 978.537.8261
Sales Fax 978.534.8362 | General Fax 978.537.5310 | www.sespoly.com

6/19/2009

The information presented here is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise. All risks of such use are assumed by the user. Furthermore, nothing contained herein shall be construed as an inducement or recommendation to use any process or to manufacture or use any product in conflict with existing or future patents.